

Part No. 38249

## 4 PORT HDMI 18G SWITCH WITH AUDIO

SWITCH BETWEEN 4 HDMI SOURCES AND EXTRACT DIGITAL AND ANALOGUE AUDIO



### DESCRIPTION

- Switch between 4 HDMI 2.0 source devices connected to a single HDMI 2.0 display
- Supports resolutions up to 4K 60Hz, with additional support for HDR
- Extract digital and analogue audio from a HDMI source device
- Seamless control via IR remote, push button, auto switching and RS232
- 2 year warranty

The Lindy 4 Port HDMI 2.0 18G Switch with Audio is a professional solution for providing simple yet reliable switching control over 4 HDMI source devices connected to a single HDMI display, while also expanding a displays HDMI port connections. Supporting HDMI 2.0 18G signals, this switch allows for the transmission of detailed 4K Ultra HD resolutions, while additional support for High-Dynamic Range ensures video content can be seen with enhanced brightness, greater contrasts and a much wider colour gamut, perfect for a premium home cinema experience, eye-catching digital signage in retail settings or engaging presentations. HDCP 2.2 support ensures there are no issues with a variety of 4K content when connected to source devices including set top boxes, Blu-Ray players and 4K HDR media players.

As well as HDMI audio pass-through, the switches 3.5mm audio port allows for a separate connection of both analogue speaker systems, and optical audio devices such as soundbars and amplifiers via the included adapter, great for ensuring a multi-channel audio experience to provide a heightened sense of realism for the viewer.

This 4 Port HDMI switch also provides a huge range of seamless control options for the user, to ensure efficient, hassle free usage for both new, and experienced users. The switch itself can be controlled manually via push button switching, while it can also identify the active HDMI source device and automatically switch to this option. The included remote control allows the user to have convenient control over multiple videos and audio formats from a distance, great for trade show demonstrations or training presentations, while the RS-232 connection can be used for professional PC control of the switch, or integrating it into other automated PC control systems.

### RELATED PRODUCTS

38244  
 38243  
 36272  
 36472  
 36474

# 4 PORT HDMI 18G SWITCH WITH AUDIO

## SPECIFICATIONS

---

AV Interface	HDMI
Interface Standards	HDMI 2.0
Supported Bandwidth	18Gbps
Maximum Resolution	3840x2160@60Hz 4:4:4 8bit
HDCP Support	2.2
Supported Audio	Audio Pass-through, Analogue 2CH, Up to 5.1CH (Optical)
Separate Audio Ports	Stereo (3.5mm), Toslink (Optical) [with included adapter]
IR Support	38kHz
CEC Support	Pass-through
Serial Interface	RS-232 (3.5mm)
Special Features	Audio EDID Management Automatic switching of active ports

## PHYSICAL PROPERTIES

---

Dimensions (approx.) WxDxH	180x85x11.6mm (7.09x3.35x0.46in)
Housing Material	Metal
Net Weight	0.563kg [1.24lb]
Operating Temperature	0°C - 40°C [32°F - 104°F]
Storage Temperature	-20°C - 60°C [-4°F - 140°F]
Humidity	20-90% RH (non-condensing)
Power Requirements	5VDC 1A
Colour	Black

## CONNECTORS

---

Input	4 x HDMI Type A (Female)
Output	HDMI Type A (Female), 3.5mm (Female)
Control	RS-232 (3.5mm), IR (3.5mm)
Power	5.5/2.1mm DC Socket

## MISCELLANEOUS

---

Packaging Type	Carton Box
Packaging Dimension	248x55x183mm (9.76x2.17x7.2in)
Gross Weight	0.682kg [1.5lb]
Warranty (Years)	2
Certificated	CE, FCC, RoHS & REACH

## PURCHASING INFORMATION

---

No.	38249
EAN	4002888382496

## PACKAGING CONTENTS

---

4 Port HDMI Switch with Audio  
 Multi-country Power Supply (UK, EU, US & AUS)  
 IR Extension Cable, 1.5m  
 Mini Optical to Optical Adapter  
 Remote Control and CR2032L Battery  
 3.5mm RS-232 Cable, 1m  
 Lindy Manual