

CLEVERTOUCH

The market leading interactive touchscreen



Clevertouch S Series

Clevertouch S Series features the latest touchscreen technology and a strong steel bezel.

- Interactive multi touch technology
- Anti glare glass
- High definition and optimal resolution 1080p
- Integrated speakers
- Freeze frame
- USB playback
- Light weight steel bezel
- Side mounted HDMI
- Side mounted USB for touch
- 3 year de-install/re-install warranty UK Mainland

Software suite included:

CLEVERLYNX

Annotation software

 **DisplayNote**

Collaboration software

Snowflake

Educational games



Multi touch



Anti glare glass



Lightweight



Low power consumption



Integrated speakers 2 x 10W



High Definition



Durability



Plug and Play

Call: +44 (0)20 8319 7777 | Email: info@clevertouch.co.uk | or visit: clevertouch.co.uk

CLEVERTOUCH

The market leading interactive touchscreen



55" Clevertouch S Series

1545003AG

Display

Diagonal size	55inch
Glass type	Anti Glare
Panel resolution	1920 x 1080
Native resolution	1920 x 1080/60Hz
Brightness (nits)	400
Contrast ratio	4000:1
Response time (grey to grey)	6.5ms
Aspect ratio	16:9
Display colours	16.7M
Viewing angle horizontal / vertical	178°/178°
Pixel pitch (mm)	0.63 (w) x 0.63 (h)
Back light unit	LED

Connectivity

Video input (analogue)	D-sub
Video input (digital)	HDMI x 3
Video output (analogue)	D-sub
Video output (digital)	HDMI
Audio input	HDMI, 3.5mm mini jack
Speaker output	6 Ohm
USB (for touch)	USB-B
USB (for media devices)	USB-A
Communication input port	RS232
Communication output port	RS232

Features

Video	Color temp.	5700(warm), 6500(medium), 9300(cool), Standard
	Progressive scan	✓
Sound	Stereo	✓
	Output	10W
	Built-in speakers	10W x 2
Function	Languages	English, Spanish, French, Dutch, Chinese(S), Chinese (T), Japanese. (Able to add new language, option)
	Auto ambience detection	✓
	IPC adaptation	✓

Power

Service and warranty	3 years
Power consumption	< 150 watts
Power consumption in standby mode	< 0.5 watts

Physical Specification

Dimensions (not incl. stand) mm	1305.94 (w) x 786.95 (h) x 110.3 (d)
Product weight	47.18
VESA mount	440 x 400
Green approvals	Lead free, RoHS compliant
Regulatory approvals	CE/FCC
Thickness of toughened glass	4mm

Touch system

Detection method	SLW - 6 point
Touch tool	Stylus, Finger, Solid Object (over 8mm nib)
Accuracy	≤3mm x 3mm
Read speed	≥100 frame/s
Response time	<10ms
Effective screen size (w x h)	1209.6 x 680.4 (mm)
Interface	USB-B
Supported OS	Windows, MAC, Linux
Touch driver for Windows	XP / Vista / 7 / 8 Plug & Play
Touch driver for Mac	Lion / Mountain Lion / Mavericks
Touch driver for Linux	Ubuntu

Accessories

UK mains lead	✓
Euro mains lead	✓
USB lead A-B	✓
HDMI lead	✓
VGA lead	✓
Stereo mini jack lead	✓
Remote control + batteries	✓
Stylus pen	✓
User manual	✓
Driver disc	Not required



65" Clevertouch S Series

1545005AG

Display

Diagonal size	65inch
Glass type	Anti Glare
Panel resolution	1920 x 1080
Native resolution	1920 x 1080/60Hz
Brightness (nits)	300 (typical)
Contrast ratio	4000:1 (typical)
Response time (grey to grey)	8ms
Aspect ratio	16:9
Display colours	1.07B
Viewing angle horizontal / vertical	178°/178°
Pixel pitch (mm)	0.744
Back light unit	LED

Connectivity

Video input (analogue)	D-sub x 1
Video input (digital)	HDMI x 3
Video output (analogue)	D-sub x 1
Video output (digital)	HDMI
Audio input	HDMI, 3.5mm mini jack
Speaker output	6 Ohm
USB (for touch)	USB-B
USB (for media devices)	USB-A
Communication input port	RS232
Communication output port	RS232

Features

Video	Color temp.	5700(warm), 6500(medium), 9300(cool), Standard
	Progressive scan	✓
Sound	Stereo	✓
	Output	10W
	Built-in speakers	10W x 2
Function	Languages	English, Spanish, French, Dutch, Chinese(S), Chinese (T), Japanese. (Able to add new language, option)
	Auto ambience detection	✓
	IPC adaptation	✓

Power

Service and warranty	3 years
Power consumption	< 250 watts
Power consumption in standby mode	< 0.5 watts

Physical Specification

Dimensions (not incl. stand) mm	1538.24 (w) x 916.55 (h) x 115.8 (d)
Product weight	63.32kg
VESA mount	440 x 400
Green approvals	Lead free, RoHS compliant
Regulatory approvals	CE/FCC
Thickness of toughened glass	5mm

Touch system

Detection method	SLW - 6 point
Touch tool	Stylus, Finger, Solid Object (over 8mm nib)
Accuracy	≤3mm x 3mm
Read speed	> 100 frame/s
Response time	< 10ms
Effective screen size (w x h)	1428.48 x 803.52 (mm)
Interface	USB-B
Supported OS	Windows, MAC, Linux
Touch driver for Windows	XP / Vista / 7 / 8 Plug & Play
Touch driver for Mac	Lion / Mountain Lion / Mavericks
Touch driver for Linux	Ubuntu

Accessories

UK mains lead	✓
Euro mains lead	✓
USB lead A-B	✓
HDMI lead	✓
VGA lead	✓
Stereo mini jack lead	✓
Remote control + batteries	✓
Stylus pen	✓
User manual	✓
Driver disc	Not required

CLEVERTOUCH

The market leading interactive touchscreen



80" Clevertouch S Series

1545016AG

Display

Diagonal size	80inch
Glass type	Anti Glare
Panel resolution	1920 x 1080
Native resolution	1920 x 1080/60Hz
Brightness (nits)	350
Contrast ratio	5000:1
Response time (grey to grey)	4ms
Aspect ratio	16:9
Display colours	16.7M
Viewing angle horizontal / vertical	176°/176°
Back light unit	LED

Connectivity

Video input (analogue)	D-sub
Video input (digital)	HDMI x 2
Video output (analogue)	D-sub
Video output (digital)	HDMI
Audio input	HDMI, 3.5mm mini jack
Speaker output	6 Ohm
USB (for touch)	USB-B
USB (for media devices)	USB-A
Communication input port	RS232
Communication output port	RS232

Features

Video	Color temp.	5700(warm), 6500(medium), 9300(cool), Standard
	Progressive scan	✓
Sound	Stereo	✓
	Output	10W
	Built-in speakers	10W x 2
Function	Languages	English, Spanish, French, Dutch, Chinese(S), Chinese (T), Japanese. (Able to add new language, option)
	Auto ambience detection	✓
	IPC adaptation	✓

Power

Service and warranty	3 years
Power consumption	< 270 watts
Power consumption in standby mode	< 0.8 watts

Physical Specification

Dimensions (not incl. stand) mm	1867 (w) x 1099 (h) x 135 (d)
Product weight	84.2kgs
VESA mount	400x400
Green approvals	Lead free, RoHS compliant
Regulatory approvals	CE/FCC
Thickness of toughened glass	5mm

Touch system

Detection method	SLW - 10 point
Touch tool	Stylus, Finger, Solid Object (over 8mm nib)
Accuracy	≤3mm x 3mm
Read speed	≥100 frame/s
Response time	<10ms
Interface	USB-B
Supported OS	Windows, MAC, Linux
Touch driver for Windows	XP / Vista / 7 / 8 Plug & Play
Touch driver for Mac	Lion / Mountain Lion / Mavericks
Touch driver for Linux	Ubuntu

Accessories

UK mains lead	✓
Euro mains lead	✓
USB lead A-B	✓
HDMI lead	✓
VGA lead	✓
Stereo mini jack lead	✓
Remote control + batteries	✓
Stylus pen	✓
User manual	✓
Driver disc	Not required