EB-L1750U



Extremely bright 15,000-lumen WUXGA 3LCD laser projector, offering outstanding fit and forget reliability with 4K enhancement technology.

Thanks to outstandingly bright 15,000-lumen WUXGA performance and rich, vivid colours as well as reliable fit and forget performance, the EB-L1750U installation laser projector is ideally suited to large rooms and venues. With flexible installation and low maintenance, this 4K-enhanced projector offers a perfect solution for scenarios where only maximum performance and durability will do.

Laser-sharp images

Ensure that your presentations, images and video pack a punch with the vivid, sharp projection offered by this 3LCD laser projector. Designed for larger venues, its high resolution WUXGA images are vivid and bright, even in daylight, while inorganic phosphor wheel technology provides superior light and heat resistance to deliver excellent reliability that lasts for up to 83,000 hours¹.

4K enhancement

For a next-level viewing experience, the projector features ingenious 4K enhancement technology, giving images exceptional sharpness and clarity, and ensuring that text in presentations is clearly legible.

Flexible positioning

Thanks to a new range of motorised lenses, including optional ultra-short-throw (UST) lens, the projector benefits from true 360° installation flexibility, allowing it to be placed virtually anywhere - without loss of brightness or distortion of image. The projector also has a built-in camera to ensure accurate calibration and capture diagnostic images (this can be fully disabled to prevent remote access).

Versatile new software

All models in the EB-L1000 series can take advantage of free Epson Professional Projector Tool software from December 2017. It allows you to set up multiprojector installations straight out of the box, simply and quickly, as well as utilising advanced techniques such as projection-mapping and edge-blending.

DATASHEET / BROCHURE



KEY FEATURES

- Laser light source technology Outstanding brightness and colour, with fit and forget reliability
- HD images with 4K enhancement Exceptional sharpness, clarity and detail for crisp images and legible text
- Versatile new software Set up multiple projector installations and utilise advanced projection techniques
- Flexible 360° installation True flexibility without distortion or loss of brightness
- Added peace of mind Product comes with five-year, 20,000hour warranty





PRODUCT SPECIFICATIONS

| TECHNOLOGY Projection System | 3LCD Technology | |
|---|--|--|
| LCD Panel | 1.03 inch with C2 Fine | |
| | | |
| IMAGE | | |
| Color Light Output | 15,000 Lumen- 10,500 Lumen (economy) In accordance with ISO 21118:2013 | |
| White Light Output | 15,000 Lumen - 10,500 Lumen (economy) In accordance with ISO 21118:2013 | |
| Portrait Colour Light Output | 15,000 lm 15,000 lm | |
| Portrait White Light Output | | |
| Resolution High Definition | WUXGA, 1920 x 1200, 16:10 4K enhancement | |
| 0 | 16:10 | |
| Aspect Ratio Contrast Ratio | | |
| Native Contrast | 2,500,000 : 1 2,000 : 1 | |
| Light source | Laser | |
| Laser Light source | 20,000 hours Durability High, 30,000 hours Durability Eco | |
| Keystone Correction | Manual vertical: $\pm 45^{\circ}$, Manual horizontal $\pm 30^{\circ}$ | |
| Colour Reproduction | Upto 1.07 billion colours | |
| | | |
| OPTICAL | | |
| Throw Ratio | 1.57 - 2.56:1 | |
| Zoom | Motorized, Factor: 1 - 1.6 | |
| Projection Lens Zoom Ratio | 1.57 - 2.56 : 1 | |
| Lens | Optical | |
| Lens Shift | Motorized - Vertical ± 60 %, horizontal ± 18 % | |
| Lens position memory | 10 positions | |
| Screen Size | 60 inches - 500 inches | |
| Projection Distance Wide | 2 m - 17.2 m | |
| Projection Distance Tele | 3.3 m - 27.8 m | |
| Projection Distance Wide/Tele | 91.99 m - 27.77 m | |
| Projection Lens F Number | 1.8 - 2.5 | |
| Projection Lens Focal Length | 36 mm - 57.35 mm | |
| Projection Lens Focus | Motorized | |
| Interchangeable Lens | Yes | |
| CONNECTIVITY | | |
| Interfaces | Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, | |
| | VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B | |
| | (Service Only) HD SDI Wireless I AN b/a/a (240Hz) (artical) | |
| | (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) | |
| Epson iProjection App | Ad-Hoc / Infrastructure | |
| Epson iProjection App | | |
| ADVANCED FEATURES | Ad-Hoc / Infrastructure | |
| ADVANCED FEATURES | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password | |
| ADVANCED FEATURES Security | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection | |
| ADVANCED FEATURES Security | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame | |
| ADVANCED FEATURES Security Other features | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory | |
| ADVANCED FEATURES Security Other features Video Color Modes | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 | |
| ADVANCED FEATURES Security Other features Video Color Modes | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Humidity | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Options | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Options | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Signage / Retail, Visitor | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Options Room Type / Application | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Signage / Retail, Visitor Attraction | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Room Type / Application | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Signage / Retail, Visitor Attraction Ceiling Mounted | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Options Room Type / Application | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Signage / Retail, Visitor Attraction | |
| ADVANCED FEATURES Security Other features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Room Type / Application | Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Signage / Retail, Visitor Attraction Ceiling Mounted | |

EB-L1750U

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)

EPSON[®]

- Computer cable
- Cable cover
- CD Manual

OPTIONAL ACCESSORIES

- Wireless LAN Adapter ELPAP10 V12H731P01
- HDBaseT Transmitter ELPHD01 V12H547041
- Ceiling Mount ELPMB48 High EB-G7000/L1000 V12H803010
- Ceiling Mount ELPMB47 Low EB-G7000/L1000 V12H802010
- Air Filter ELPAF51
 V13H134A51
- Stacking Frame ELPMB59 L1000 Series (EVO) V12H996B59

OPTIONAL LENSES

- Lens ELPLU03S L & G Series ST off axis 1 V12H004UA3
- Lens ELPLX02 UST Lens L1500/1700 Series V12H004X02
- Lens ELPLW06 L1500U/1505U wide zoom 2 V12H004W06
- Lens ELPLW05 G7000 & L1000 Series wide zoom 1 V12H004W05
- Lens ELPLU04 G7000 & L1000 Series ST off axis 2 V12H004U04
- Lens ELPLU03 G7000 & L1000 Series ST off axis 1 V12H004U03
- Lens ELPLM15 Mid Throw L1500/L1700 Series V12H004M0F
- Lens ELPLM11 Mid throw 4 G7000/L1000 series V12H004M0B
- Lens ELPLM10 Mid throw 3 G7000/L1000 series V12H004M0A
- Lens ELPLL08 Long throw G7000/L1000 series V12H004L08
- Lens ELPLW08 Wide throw V12H004W08
- Lens ELPLX02W UST Lens L1500/1700 Series V12H004Y02

LOGISTICS INFORMATION

| SKU | V11H892040 |
|-------------------|---------------|
| EAN code | 8715946646947 |
| Country of Origin | China |
| Layer | 1 Units |
| Layer Block | 1 Units |

1. - Laser life of up to 83,000 hours in custom mode.



EB-L1750U

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice. Last extracted: 2020-01-28