



Casio Green Slim Series

The ideal replacement projectors

The Green Slim series is the perfect choice for those looking to upgrade their existing installed projectors. An industry-leading 2x optical zoom means that a Green Slim model will replace any installed projector seamlessly, without having to change the ceiling brackets. This will help to keep budgets under control and disruption to a minimum.

The Green Slim series offers brightness levels up to 3,000 ANSI lumens – more than enough for even a large, bright meeting room – and a choice of XGA & WXGA resolution. All models have HDMI connectivity, enabling the presentation of HD content. They're light and portable, so can easily be moved between rooms if required.

New features include:

- Logo transfer/ firmware update through Micro USB port
- Lower power consumption
- Made in Japan

Models	USB/ WLAN	ANSI lumens	Resolution
XJ-A257	Yes	3,000	WXGA
XJ-A247		2,500	
XJ-A147		2,500	XGA
XJ-A252	No	3,000	WXGA
XJ-A242		2,500	
XJ-A142		2,500	XGA
XJ-A132		2,000	























Key features

- Lamp-free Laser & LED Hybrid Light Source
- Up to 3,000 ANSI lumens
- 2x optical zoom
- Quick start & stop



available on both hardware and light source for ALL of our projectors.



Technical Specifications

		XJ-A132	XJ-A142, XJ-A147	XJ-A242, XJ-A247	XJ-A252, XJ-A257	
Display	Technology:	0.55" D	0.55" DLP® chip		0.65" DLP® chip	
	Resolution:	X	XGA		WXGA	
		1,024 x 768 pixels		1,280 x 800 pixels		
	Brightness:	2,000 ANSI lumens	2,500 ANSI lumens	2,500 ANSI lumens	3,000 ANSI lumens	
Light source	Туре:	Laser & LED Hybrid technology				
	Life expectancy:	Approx. 20,000 hours				
Projected image	Contrast ratio:	1,800 : 1				
	Colour depth:	16.7 million colours				
Projection lens	Туре:	2x optical zoom (electronic)				
	Projection ratio:	1.4 - 2.8 : 1 (distance : image width)		1.15 - 2.3 : 1 (distance : image width)		
	Offset:	50%		33%		
	Min. distance:	0.84m				
	Focus:	Electronic				
Projection	Projection screen size:	15" - 300"		18" - 300"		
	60" screen (diagonal):	1.7 - 3.4m distance		1.4 - 2.8m distance		
	100" screen (diagonal):	2.8 - 5.6m distance		2.4 - 4.8m distance		
Keystone correction	Vertical (automatic/manual):	+/- 30° (Auto)				
Interface terminals	Computer:	Inputs: 1 x 15-pin RGB mini D-sub (VGA)				
	Digital input:	1 x HDMI type A (480p-1,080p)				
	Video:	1 x RCA composite (via supplied AV cable)				
	Component video:	Via D Sub 15-pin				
	Audio:	Output: From HDMI input only				
	RS-232C serial:	YK-60 (optional accessory)				
	USB1:	1 x USB type A Micro-USB type-B x 1: Logo transfer/Firmware update				
	Wireless Capability (USB models only):	Wireless LAN Adapter (YW-40) is included with USB Models (802.11 b/g/n)				
Additional functions		Direct Power On, Direct Power Off, rear projection, image freeze, blank screen, ceiling mount				
Audio Volume	Speaker output:	1 W				
	Operating noise:	33 dB (default mode) / 28 dB (safe mode)				
Power consumption	Operating:		right Mode Eco Mode	165 W - Bright Mode 120 W - Eco Mode		
	Standby (*100 to 120V):	0.14 W				
	Standby (*220 to 240V):	0.23 W				
Computer compatibility	Max. resolution (compressed):	UXGA (1,600 x 1,200 pixels)				
Video compatibility	Video standards:	PAL-N, PAL-M, PAL 60, SECAM, NTSC				
	Signals:	Composite video, YCbCr, YPbPr				
On-screen menu	Languages:	Japanese, English, Spanish, German, Italian, French, Swedish, Chinese (simplified/traditional), Korean, Turkish, Portuguese, Russian				
Included accessories		Wireless remote control, RGB cable, AV cable, AC Power Cord, Carry Bag and Setup Manual (Printed)				
Other specs	Dimensions (w x h x d):	297 x 43 x 210 mm				
	Weight:	2.3 kg				
	Body colour:	White				
	Operating temperature:	5–35 °C				
	Warranty:	Projector & Light source: 5 years or 10,000 hours (whichever comes first. T&Cs apply)				

USB models only.
Functionality can only be guaranteed for products specifically designated by CASIO.
Visit the CASIO website for more details about the USB flash drives supported by this device.



