

EB-1460Ui



Develop a truly forward-thinking workplace by promoting efficient and collaborative meetings to drive knowledge sharing and communication

Bring interactivity to any meeting room with our latest ultra-short-throw projector, featuring finger-touch and dual pen capability, a high brightness level of 4,400 lumens, Full HD WUXGA resolution and remote multi-location connectivity. The ultra-short-throw EB-1460Ui is designed to present a scalable screen size of up to 100 inches to deliver the requirements of any business working environment.

Up to 100-inch display and outstanding quality

Full HD WUXGA resolution combined with Epson's 3LCD technology ensures high-quality content has more vivid colours and brighter images. HDMI connectivity also means that the audience benefits from sharper and clearer content displayed in any meeting room environment.

All in one office solution

This interactive meeting room solution combines the benefits of flipcharts, whiteboards and conventional screens into one unified meeting room solution. Meeting participants can view and annotate whiteboard content from a range of smart devices, without the need for any special application and this ensures information remains secure with the ability to apply passwords to meetings and notes.

Finger-touch and dual pen

Use your fingers to annotate directly on the screen. Epson's interactive pens are now even more responsive and easy to use. With the new dual pens, colleagues can work simultaneously using different pen attributes.



DATASHEET



KEY FEATURES

- **Up to 100-inch display & outstanding quality**
Full HD WUXGA resolution with Epson's 3LCD technology
- **All-in-one office solution**
Various office equipment in one interactive collaboration device
- **Increase integration and collaboration**
Share content from a range of devices simultaneously
- **Finger-touch and dual pen**
Use your fingers to annotate directly onto the screen
- **Whiteboard sharing mode**
Invite and share meetings notes with participants



EPSON
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology
LCD Panel	0.67 inch with MLA (D10)
IMAGE	
Colour Light Output	4,400 lumen- 2,900 lumen (economy)
White Light Output	4,400 lumen - 2,900 lumen (economy) In accordance with ISO 21118:2012
Resolution	WUXGA, 1920 x 1200, 16:10
Contrast Ratio	16,000 : 1
Native Contrast	300 : 1
Lamp	300 W, 5,000 h durability, 10,000 h durability (economy mode)
Keystone Correction	Manual vertical: $\pm 3^\circ$, Manual horizontal $\pm 3^\circ$
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Projection Ratio	0.27 - 0.37:1
Zoom	Digital, Factor: 1 - 1.35
Image Size	70 inches - 100 inches
Projection Distance Wide	0.4 m (70 inch screen)
Projection Distance Tele	0.6 m (100 inch screen)
Projection Lens F Number	1.6
Focal Distance	4.2 mm
Focus	Manual
Offset	5.8 : 1
CONNECTIVITY	
USB Display Function	3 in 1: Image / Mouse / Sound
Interfaces	USB 2.0 Type A (2x), USB 2.0 Type B, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11b/g/n, VGA in (2x), VGA out, HDMI in (2x), S-Video in, MHL, Stereo mini jack audio out, Stereo mini jack audio in (2x), Microphone input, Finger-touch interface, Sync. in, Sync. out, Miracast, Remote Desktop Protocol, USB Interface for keyboard
Epson iProjection App	Ad-Hoc / Infrastructure
ADVANCED FEATURES	
Security	Kensington lock, Password lock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection
Features	AV Mute Slide, Auto Calibration, Auto brightness adjustment, Automatic input selection, Built-in speaker, CEC compatible, Customizable user logo, Digital zoom, Direct Power on/off, Document Camera Compatible, Driverless installation, Dual Pen Support, Dynamic lamp control, Easy OSD pre-setting, Finger-touch support, Home Screen, Interactive, Long lamp life, MHL audio/video interface, Multi-screen interactivity, Mute key, PC free annotation, iProjection App for Chromebook, Remote Desktop Protocol, Screen Mirroring, Split-Screen-Function, Whiteboard sharing function, Wireless LAN capable, iProjection App
Interactivity	Yes - pen and finger-touch
Video Colour Modes	Blackboard, Dynamic, Photo, Presentation, sRGB, Whiteboard
GENERAL	
Energy Use	490 W, 400 W (economy), 0.5 W (standby)
Product dimensions	474 x 447 x 130 mm (Width x Depth x Height)
Product weight	8.5 kg
OTHER	
Warranty	36 months On site service or 8,000 h, Lamp: 12 months or 1,000 h

EB-1460Ui

WHAT'S IN THE BOX

- Remote control incl. batteries
- Control pad
- CD Manual
- Finger touch unit
- Interactive pens
- Power cable
- USB cable
- Wall mounting bracket
- Pen case
- Warranty card
- Quick Start Guide
- Wireless LAN unit
- Replacement pen tips

OPTIONAL ACCESSORIES

- Active Speakers (2 x 15W) - ELPSP02
V12H467040DA
- Control and Connection Box - ELPCB02
V12H614040DA
- Interactive Pen - ELPPN05A - Orange - EB-6xxWi/Ui / 14xxUi
V12H773010
- Air Filter - ELPAF45
V13H134A45
- Lamp - ELPLP92 - EB-69x/14x (268W)
V13H010L92
- Interactive Pen - ELPPN05B - Blue - EB-6xxWi/Ui / 14xxUi
V12H774010
- Table Mount for Ultra-short-throw Series - ELPMB29
V12H516040
- Replacement Pen Tip - ELPPS03 (Teflon)
V12H775010
- Replacement Pen Tip - ELPPS04 (Felt)
V12H776010

EB-1460Ui

LOGISTICS INFORMATION

SKU	V11H726041
EAN code	8715946610290
Country of Origin	China



For more information please contact:

Telephone: 01952 607111 (UK)+
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740
+ Local call rate.

Web: www.epson.co.uk
www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

1. - Compared to leading 1-chip DLP business and education projectors based on NPD data, July 2011 through June 2012. Colour Brightness (Colour Light Output) measured in accordance with IDMS 15.4. Colour Brightness will vary depending on usage conditions. For more information please visit www.epson.eu/CLO
2. - iProjection App available on Android and iOS devices

EPSON®